# SIGMA-ALDRICH

sigma-aldrich.com

## SAFETY DATA SHEET

Version 4.7 Revision Date 07/09/2015 Print Date 06/20/2016

## 1. PRODUCT AND COMPANY IDENTIFICATION

1.1	Product identifiers Product name	:	Ethanol	
	Product Number Brand Index-No.	:	34923 Sigma-Aldrich 603-002-00-5	
	CAS-No.	:	64-17-5	
1.2	Relevant identified uses of the substance or mixture and uses advised agains			
	Identified uses	:	Laboratory chemicals, Manufacture of substances	
1.3	Details of the supplier of the safety data sheet			
	Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA	
	Telephone Fax	:	+1 800-325-5832 +1 800-325-5052	
1.4	Emergency telephone nun	nbe	r	

### 1.4 Emergency telephone numb

Emergency Phone # : (314) 776-6555

## 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s) H225 H319	Highly flammable liquid and vapour. Causes serious eye irritation.
Precautionary statement(s)	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash skin thoroughly after handling.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing.

	Rinse skin with water/shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 **Substances**

Synonyms	: Ethyl alcohol
Formula	: C <sub>2</sub> H <sub>6</sub> O
Molecular weight	: 46.07 g/mol
CAS-No.	: 64-17-5
EC-No.	: 200-578-6
Index-No.	: 603-002-00-5
Registration number	: 01-2119457610-43-XXXX

## Hazardous components

Flam. Liq. 2; Eye Irrit. 2A;	<= 100 %
H225, H319	

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

## **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

## If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

## In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

## In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

## If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### Indication of any immediate medical attention and special treatment needed 4.3 No data available

## 5. FIREFIGHTING MEASURES

#### 5.1 **Extinguishing media**

## Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### 5.2 Special hazards arising from the substance or mixture Carbon oxides

## 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

## 5.4 Further information

Use water spray to cool unopened containers.

## 6. ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

## 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

## 6.3 Methods and materials for containment and cleaning up Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

## 6.4 Reference to other sections

For disposal see section 13.

## 7. HANDLING AND STORAGE

## 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

hygroscopic Storage class (TRGS 510): Flammable liquids

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters

## Components with workplace control parameters

· · · · · · · · · · · · · · · · · · ·	workplace cor	<u> </u>		
Component	CAS-No.	Value	Control	Basis
			parameters	
Ethonol	64-17-5	TWA		USA. ACGIH Threshold Limit Values
Ethanol	04-17-5	IVVA	1,000.000000	
			ppm	(TLV)
	Remarks	Upper Res	spiratory Tract irritat	ion
		Confirmed animal carcinogen with unknown relevance to humar		
		TWA 1,000 ppm USA. OSHA - TABLE 2		USA. OSHA - TABLE Z-1 Limits for
			1,900 mg/m3 Air Contaminants - 1910.1000	
		TWA	1,000 ppm	USA. Occupational Exposure Limits
			1,900 mg/m3	(OSHA) - Table Z-1 Limits for Air
		.,		Contaminants
		The value	in mg/m3 is approx	imate.
		TWA	1,000.000000 USA. Occupational Exposure Li	
			ppm	(OSHA) - Table Z-1 Limits for Air
			1,900.000000	Contaminants
			mg/m3	
		The value	in mg/m3 is approx	imate.

TWA	1,000.000000 ppm 1,900.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
STEL	1,000.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
Upper Respiratory Tract irritation Confirmed animal carcinogen with unknown relevance to humans		

## **Derived No Effect Level (DNEL)**

Application Area	Exposure routes	Health effect	Value
Workers	Inhalation	Long-term systemic effects	950 mg/m3
Workers	Skin contact	Long-term systemic effects	343mg/kg BW/d
Workers	Ingestion	Long-term systemic effects	343mg/kg BW/d
Workers	Inhalation	Acute local effects	1900 mg/m3

## Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0.63 mg/kg
Marine water	0.79 mg/l
Fresh water	0.96 mg/l
Fresh water sediment	3.6 mg/l
Sewage treatment plant	580 mg/l

## 8.2 Exposure controls

## Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

## Personal protective equipment

## Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

## **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.2 mm Break through time: 38 min Material tested:Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

## **Body Protection**

impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

## **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

## **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid, clear Colour: colourless	
b)	Odour	No data available	
c)	Odour Threshold	No data available	
d)	рН	No data available	
e)	Melting point/freezing point	Melting point/range: -114 °C (-173 °F)	
f)	Initial boiling point and boiling range	78 °C (172 °F)	
g)	Flash point	14.0 °C (57.2 °F) - closed cup	
h)	Evaporation rate	No data available	
i)	Flammability (solid, gas)	No data available	
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 19 %(V) Lower explosion limit: 3.3 %(V)	
k)	Vapour pressure	59.5 hPa (44.6 mmHg) at 20.0 °C (68.0 °F)	
I)	Vapour density	No data available	
m)	Relative density	0.789 g/mL at 25 °C (77 °F)	
n)	Water solubility	completely soluble	
o)	Partition coefficient: n- octanol/water	log Pow: -0.349 at 24 °C (75 °F)	
p)	Auto-ignition temperature	363.0 °C (685.4 °F)	
q)	Decomposition temperature	No data available	
r)	Viscosity	No data available	
s)	Explosive properties	No data available	
t)	Oxidizing properties	No data available	
Other safety information No data available			

## **10. STABILITY AND REACTIVITY**

## 10.1 Reactivity

9.2

No data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.
- **10.4 Conditions to avoid** Heat, flames and sparks.
- **10.5** Incompatible materials Alkali metals, Oxidizing agents, Peroxides
- **10.6 Hazardous decomposition products** Other decomposition products - No data available In the event of fire: see section 5

## **11. TOXICOLOGICAL INFORMATION**

## 11.1 Information on toxicological effects

## Acute toxicity

LD50 Oral - Rat - 10,470 mg/kg

LC50 Inhalation - Rat - 4 h - 30,000 mg/l

LD50 Dermal - Rabbit - 15,800 mg/kg

No data available

## Skin corrosion/irritation

Skin - Rabbit Result: No skin irritation - 24 h (OECD Test Guideline 404)

## Serious eye damage/eye irritation

Eyes - Rabbit Result: Moderate eye irritation (OECD Test Guideline 405)

**Respiratory or skin sensitisation** No data available

Germ cell mutagenicity No data available

## Carcinogenicity

Carcinogenicity - Mouse - Oral Tumorigenic:Equivocal tumorigenic agent by RTECS criteria. Liver:Tumors. Blood:Lymphomas including Hodgkin's disease.

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

## **Reproductive toxicity**

## No data available

Reproductive toxicity - Human - female - Oral Effects on Newborn: Apgar score (human only). Effects on Newborn: Other neonatal measures or effects. Effects on Newborn: Drug dependence.

## Specific target organ toxicity - single exposure

No data available

## Specific target organ toxicity - repeated exposure

No data available

## Aspiration hazard

No data available

## **Additional Information**

RTECS: KQ6300000

Central nervous system depression, narcosis, Damage to the heart., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

## **12. ECOLOGICAL INFORMATION**

## 12.1 Toxicity

Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) - 14,200 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates	LC50 - Ceriodaphnia dubia (water flea) - 5,012 mg/l - 48 h
	NOEC - Daphnia magna (Water flea) - 9.6 mg/l - 9 d
Toxicity to algae	EC50 - Chlorella vulgaris (Fresh water algae) - 275 mg/l - 72 h (OECD Test Guideline 201)

## 12.2 Persistence and degradability

Biodegradability Result: 95 % - Readily biodegradable

## 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

## 12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

## 12.6 Other adverse effects

No data available

## **13. DISPOSAL CONSIDERATIONS**

## 13.1 Waste treatment methods

## Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

## Contaminated packaging

Dispose of as unused product.

## 14. TRANSPORT INFORMATION

## DOT (US)

UN number: 1170 Class: 3 Proper shipping name: Ethanol Reportable Quantity (RQ): Packing group: II

Poison Inhalation Hazard: No

## IMDG

UN number: 1170 Class: 3 Proper shipping name: ETHANOL EMS-No: F-E, S-D

## **15. REGULATORY INFORMATION**

## SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

## SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

## Massachusetts Right To Know Components

CAS-No.	Revision Date
64-17-5	2007-03-01
CAS-No.	Revision Date
64-17-5	2007-03-01
CAS-No.	Revision Date
64-17-5	2007-03-01
	64-17-5 CAS-No. 64-17-5 CAS-No.

## California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## **16. OTHER INFORMATION**

## Full text of H-Statements referred to under sections 2 and 3.

Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.

## **HMIS Rating**

Health hazard:	2
Chronic Health Hazard:	
Flammability:	3
Physical Hazard	

## **NFPA** Rating

Health hazard:	2
Fire Hazard:	3
Reactivity Hazard:	
Health hazard:	2
Fire Hazard:	
Reactivity Hazard:	

## **Further information**

Copyright 2015 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

**Preparation Information** Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 4.7

Revision Date: 07/09/2015

Print Date: 06/20/2016